

EASY SELECTION GUIDE FOR MACHINE AND PANEL BUILDERS

# Connects I/O Block & Cable Stocking Program

IN STOCK. SHIPPED FAST. COMPETITIVELY PRICED.



## Easy Selection Guide for MACHINE BUILDERS

**M12, 4 Pin, A Coded, PUR Cable, Black Jacket, 24AWG Wires**  
 Most Common Usage: Sensors, Switches, IO Devices, IO Link

	Connector A	Connector B	Length	Model Code		
	Female 0°	Male 0°			2m	BCC039M
	Female 0°	Male 0°			3m	BCC039N
	Female 0°	Male 0°			5m	BCC039P
	Female 0°	Male 0°			10m	BCC06WR
	Female 0°	Male 0°			15m	BCC0E9U

	Connector A	Connector B	Length	Model Code		
	Female 0°	Open			5m	BCC032H
	Female 0°	Open			10m	BCC032J
	Female 0°	Open			15m	BCC06TP

	Connector A	Connector B	Length	Model Code		
	Female 90°	Male 0°			3m	BCC03AF
	Female 90°	Male 0°			5m	BCC03AH
	Female 90°	Male 0°			10m	BCC0AFE

	Connector A	Connector B	Length	Model Code		
	Female 90°	Open			5m	BCC032Z
	Female 90°	Open			15m	BCC06U0

	Connector A	Connector B	Length	Model Code		
	Male 0°	Open			5m	BCC031P
	Male 0°	Open			10m	BCC031R
	Male 0°	Open			15m	BCC0HM3

	Connector A	Connector B	Length	Model Code		
	Male 90°	Open			5m	BCC0322
	Male 90°	Open			15m	BCC0K7U




	Connector A	Connector B	Length	Model Code
	Female 0°	NA		

	Connector A	Connector B	Length	Model Code
	Male 0°	NA		




800-569-9801 • [info@evolutionmotion.com](mailto:info@evolutionmotion.com)  
[evolutionconnects.com](http://evolutionconnects.com)






## Most Common Usage: Solenoid Valves, Analog Devices, Safety Devices, Grounded Devices

			Length	Model Code
	Connector A	Connector B		
	Female 0°	Male 0°		
			5m	BCC09FU
			10m	BCC0FOA




  

			Length	Model Code
	Connector A	Connector B		
	Male 90°	Open		
			5m	BCC08FC
			10m	BCC08F7




  

			Length	Model Code
	Connector A	Connector B		
	Male 0°	Open		
			5m	BCC08JC
			10m	BCC08JA




  

			Length	Model Code
	Connector A	Connector B		
	Male 0°	NA		
			NA	BCC06YA

			Length	Model Code
	Connector A	Connector B		
	Female 0°	Open		
			5m	BCC098C
			10m	BCC0860

			Length	Model Code
	Connector A	Connector B		
	Female 0°	NA		
			NA	BCC06ZF

## M12, 5 Pin, Shielded, A Coded, PUR Cable, Black Jacket, 24AWG Wires

Most Common Usage: Analog Devices "0-10V"




			Length	Model Code
	Connector A	Connector B		
	Male 0°	Open		
			5m	BCC0H50
			10m	BCC09K1




			Length	Model Code
	Connector A	Connector B		
	Female 0°	Open		
			5m	BCC08KP
			10m	BCC08KR

## 7/8", 4 Pin, TPE Cable, Yellow Jacket, 16AWG Wires

Most Common Usage: 24VDC Power




			Length	Model Code
	Connector A	Connector B		
	Female 0°	Male 0°		
		2m	BCC0A8T	
		3m	BCC0C9A	
		5m	BCC0A8U	
		10m	BCC0A8W	
		15m	BCC0A8Y	
		20m	BCC0A8Z	




  

			Length	Model Code
	Connector A	Connector B		
	Female 0°	Open		
			5m	BCC0A8E
			10m	BCC0A8F

### M12, 4 Pin, D Coded, TPE Cable, Teal Jacket




Most Common Usage: Fast Ethernet "Cat 5e" (Ethernet IP, Ethercat, Profinet)




			Length	Model Code
	Connector A	Connector B		
	Male 0°	Male 0°	2m	BCC09NN
	Male 0°	Male 0°	3m	BCC0CEC
	Male 0°	Male 0°	5m	BCC09NP
	Male 0°	Male 0°	10m	BCC09NR
	Male 0°	Male 0°	15m	BCC09NT
	Male 0°	Male 0°	20m	BCC09NU

			Length	Model Code
	Connector A	Connector B		
	Male 0°	RJ45 0°	5m	BCC0E8Z
	Male 0°	RJ45 0°	10m	BCC0E8P

### M12, 8 Pin, X Coded, PUR Cable, Green Jacket





Most Common Usage: Gigabit Ethernet "Cat 6" (Ethernet IP, Ethercat, Profinet)

			Length	Model Code
	Connector A	Connector B		
	Male 0°	Male 0°	2m	BCC0HZP
	Male 0°	Male 0°	5m	BCC0HZR
	Male 0°	Male 0°	10m	BCC0HZT
	Male 0°	Male 0°	15m	BCC0JNY
	Male 0°	Male 0°	20m	BCC0JNZ

			Length	Model Code
	Connector A	Connector B		
	Male 0°	RJ45 0°	5m	BCC0HZL
	Male 0°	RJ45 0°	10m	BCC0HZM





### M12, 4 Pin, Tee

Most Common Usage: IO Block Single Port Tee

				Model Code
	Connector A	Connector B	Connector C	
	Male M12, 5 Pin, A Coded	Female M12, 4 Pin A Coded	Female M12, 4 Pin A Coded	BCC089P





### 7/8", 4 Pin, Tee

Most Common Usage: 24VDC Power

				Model Code
	Connector A	Connector B	Connector C	
	Male 0°	Male 0°	Female 0°	BCC0AA6

### Ethernet IP IO Block, 16 Configurable PNP Inputs/Outputs, 8 IO Link Ports



Most Common Usage: Networking IO

				Model Code
	Power Connection	Ethernet Connection	IO Ports	
	7/8"	M12 Female D Coded	5 Pin A Coded Female	BNI006A

# Easy Selection Guide for PANEL BUILDERS



## M12, 4 Pin, Female, A Coded, Flying Leads, M16 x 1.5mm Mounting, 24AWG Wires

Most Common Usage: Panel Sensor Connections

		Pin 1 - Brown - power Pin 2 - White - signal Pin 3 - Blue - power Pin 4 - Black - signal Pin 5 - Gray - ground or signal		
	Connector A	Connector B	Length	Model Code
	Female 0°	Flying Leads	.2m	BCC08M2
	Female 0°	Flying Leads	.5m	BCC099C
Female 0°	Flying Leads	2.0m	BCC0CAE	



## 7/8", 4 Pin, Female, Flying Leads, 1/2" NPT Mounting, 16AWG Wires

Most Common Usage: 24V Remote Power

		Pin 1 - Brown - power Pin 2 - White - signal Pin 3 - Blue - power Pin 4 - Black - signal		
	Connector A	Connector B	Length	Model Code
	Female 0°	Flying Leads	.6m	BCC0E63
	Female 0°	Flying Leads	2.0m	BCC0720



## M12, 4 Pin, Male, A Coded, Flying Leads, M16 x 1.5mm Mounting, 24AWG Wires

Most Common Usage: Panel Sensor Connections

		Pin 1 - Brown - power Pin 2 - White - signal Pin 3 - Blue - power Pin 4 - Black - signal		
	Connector A	Connector B	Length	Model Code
	Male 0°	Flying Leads	.2m	BCC08M1
	Male 0°	Flying Leads	.5m	BCC099A
Male 0°	Flying Leads	2.0m	BCC0E53	



## 7/8", 4 Pin, Male, Flying Leads, 1/2" NPT Mounting, 16AWG Wires

Most Common Usage: 24V Remote Power

		Pin 1 - Brown - power Pin 2 - White - signal Pin 3 - Blue - power Pin 4 - Black - signal		
	Connector A	Connector B	Length	Model Code
	Male 0°	Flying Leads	.6m	BCC0E64
	Male 0°	Flying Leads	2.0m	BCC0722




## M12, 5 Pin, Female, A Coded, Flying Leads, M16 x 1.5mm Mounting, 24AWG Wires

Most Common Usage: Panel Sensor Connections

		Pin 1 - Brown - power Pin 2 - White - signal Pin 3 - Blue - power Pin 4 - Black - signal Pin 5 - Gray - ground or signal		
	Connector A	Connector B	Length	Model Code
	Female 0°	Flying Leads	.5m	BCC09JZ
	Female 0°	Flying Leads	2.0m	BCC0E54



## M12, 4 Pin, D Coded, PUR Cable, Green Jacket

Most Common Usage: Fast Ethernet "Cat 5e"  
(Ethernet IP, Ethercat, Profinet)

				
	Connector A	Connector B	Length	Model Code
	Female 0°	RJ45 0°	.6m	BCC0FYW
	Female 0°	RJ45 0°	1m	BCC0HH5
Female 0°	RJ45 0°	2m	BCC0FYY	
Female 0°	RJ45 0°	5m	BCC0FYZ	




## M12, 5 Pin, Male, A Coded, Flying Leads, M16 x 1.5mm Mounting, 24AWG Wires

Most Common Usage: Panel Sensor Connections

		Pin 1 - Brown - power Pin 2 - White - signal Pin 3 - Blue - power Pin 4 - Black - signal Pin 5 - Gray - ground or signal		
	Connector A	Connector B	Length	Model Code
	Male 0°	Flying Leads	.5m	BCC09K0
	Male 0°	Flying Leads	2.0m	BCC0E5F

## M12, 8 Pin, x Coded, TPE Cable, Green Jacket

Most Common Usage: Fast Ethernet "Cat 5e"  
(Ethernet IP, Ethercat, Profinet)

				
	Connector A	Connector B	Length	Model Code
	Female 0°	RJ45 0°	.6m	BCC0LJP
	Female 0°	RJ45 0°	1m	BCC0LJR
Female 0°	RJ45 0°	2m	BCC0LJT	
Female 0°	RJ45 0°	5m	BCC0LJU	

