


Aluminum Extrusion Stocking Program

CUT-TO-LENGTH. IN STOCK. COMPETITIVELY PRICED.

The Aluminum Extrusion Stocking Program features cut-to-length Bosch Rexroth aluminum profiles for strong, reliable, and safe applications such as shelves, safety fences, and machine frames. The product portfolio includes a variety of cross-sections, connectors, and fasteners in stock at a competitive price.



Cross-Sections




30x30 Strut

PART NUMBERS:

3 842 557 216 (1 Piece)
3 842 990 720 / L (1 Stick Cut to Length)
3 842 557 206 (20 ct. Bundle)

TECHNICAL DATA:

Inertia: 3.1 cm⁴, **Area:** 2.8 cm²,
Weight: 0.9 kg/m, **Slot Width:** 8 mm




45x45L Strut

PART NUMBERS:

3 842 553 618 (1 Piece)
3 842 992 425 / L (1 Stick Cut to Length)
3 842 553 611 (20 ct. Bundle)

TECHNICAL DATA:

Inertia: 11.7 cm⁴, **Area:** 6.0 cm²,
Weight: 1.6 kg/m, **Slot Width:** 10 mm




90x90L Strut

PART NUMBERS:

3 842 553 620 (1 Piece)
3 842 992 415 / L (1 Stick Cut to Length)
3 842 553 613 (6 ct. Bundle)

TECHNICAL DATA:

Inertia: 211.1 cm⁴, **Area:** 24.1 cm²,
Weight: 6.5 kg/m, **Slot Width:** 10 mm




30x60 Strut

PART NUMBERS:

3 842 557 215 (1 Piece)
3 842 992 457 / L (1 Stick Cut to Length)
3 842 557 205 (20 ct. Bundle)

TECHNICAL DATA:

Inertia: 19.6 cm⁴, **Area:** 5.5 cm²,
Weight: 1.5 kg/m, **Slot Width:** 8 mm




45x60 Strut

PART NUMBERS:

3 842 557 210 (1 Piece)
3 842 990 570 / L (1 Stick Cut to Length)
3 842 557 200 (20 ct. Bundle)

TECHNICAL DATA:

Inertia: 37.2 cm⁴, **Area:** 11.0 cm²,
Weight: 3.0 kg/m, **Slot Width:** 10 mm



45x90L Strut

PART NUMBERS:

3 842 553 619 (1 Piece)
3 842 992 432 / L (1 Stick Cut to Length)
3 842 553 612 (6 ct. Bundle)

TECHNICAL DATA:

Inertia: 82.0 cm⁴, **Area:** 11.3 cm²,
Weight: 3.0 kg/m, **Slot Width:** 10 mm


800-569-9801 • info@evolutionmotion.com
evolutionmotion.com/products/aluminum-extrusion-stocking-program



*Not available in Michigan, Northern Ohio, and Canada

Connectors & Fasteners

The Aluminum Extrusion Stocking Program offers connectors and fasteners that are quick and easy to install for a strong, secure connection. These connectors are self-adjusting, safe against twisting, torsion proof, and vibration proof. The well-designed and highly rigid connectors provide quick and precise installation for a reliable connection of aluminum extrusions.




Cubic Connector Kits

- High rigidity
- Quick installation
- Gap-free mounting

PART NUMBERS:

30/2 -	3 842 549 862
30/3 -	3 842 549 864
45/2 -	3 842 549 870
45/3 -	3 842 598 872




Quick Connector

- Easy & quick installation
- Free slots for panel mounting
- Movable on profile slot

PART NUMBERS:

N8 0° 8/8 -	3 842 535 459
N8 90° 8/8 -	3 842 535 465
N10 0° 10/10 -	3 842 535 458
N10 90° 10/10 -	3 842 535 466




Gusset Kits

- Quick & precise installation
- Plug-through screws

PART NUMBERS:

30x30 8/8 slot -	3 842 523 528
30x60 8/8 slot -	3 842 523 541
45x45 10/10 slot -	3 842 523 561
45x90 10/10 slot -	3 842 523 570
90x90 10/10 slot -	3 842 523 578



T-Bolts Kits

- Strong & reliable connection
- High torsion resistance

PART NUMBERS:

M 6X20 -	8 981 019 578
M 8X21 -	8 981 021 343



T-Nut

- Very high load-bearing capacity
- Quick & exact installation

PART NUMBERS:

8 mm slot -	3 842 501 753
10 mm slot -	3 842 530 287

